



产品特性/Product Features

- IP6K9K
- 100A 85°C
- 12-750VDC
- 1000MΩ (1000VDC) , IEC 60664-1

触点参数 / Contact parameters

		1a	
		≤3mΩ (at 20A)	
		100A	
		2×10 ⁵	
		450V型	750V型
		1000VDC	1000VDC
		1000A(320VDC)1	1000A(320VDC)1
		45kW	75kW
1)		2×10 ⁻⁴ 22.5VDC, =1ms 400A, 100A	2×10 ⁻⁴ 37.5VDC, =1ms 400A, 100A
		1 360VDC, =1ms 1350A, 100A	
		1×10 ⁻⁴ 360VDC,50A	6×10 ⁻³ 600VDC,50A
		: 3×10 ⁻³ 450VDC,100A	: 1×10 ⁻³ 750VDC,100A
2)		100A:	
		120A:2h	
		200A:10min	
		400A:2min	
		600A:30s	
		1000A:0.6s	

1) 23°C, 0.6s:5.4s.

2) 85°C, 40 mm², " "

性能参数 / Performance parameters

		1000M Ω (1000VDC)
		3000VAC 1min
		3000VAC 1min
	()	≤ 30 ms
	()	≤ 10 ms
		196m/s ²
		490m/s ²
		10Hz ~ 500Hz 49m/s ²
		5% ~ 85%RH
		-40°C ~ 85°C
		M5
		350g
		76.5mm \times 39.0mm \times 77.0mm

线圈参数 / Coil parameters

12	9	1	4.5
24	≤ 18	≥ 2	4.5

-40°C ~ 85°C)

外形图、安装孔尺寸 / Outline drawing, mounting hole size

/Unit mm



